

Features :

- Low-cost solution for a winch with 720 mm long jib crane supplied with clamps for fixing on scaffolding
- Noise level 72 db(A)
- Electrical upper limit switch device
- Protection against the phenomenon of overspeed (self-generation) when lowering in the event of a break in the electricity supply
- Protection against on-site voltage variations (210/235 V)
- Oil-immersed geared motor
- Electrical cables in neoprene sheaths for improved resistance to low temperatures up to -25°C
- Patented safety device keeping two turns of steel wire rope constantly wound on the drum to prevent force being applied to the wire rope attachment point
- Supply voltage 230 V single phase 50 Hz
- Direct voltage control via pendant control station with 2 buttons + emergency stop (IP 65 protection) with 1.50 m control cable

Options :

- Fixings for scaffolding, window strut, stand (see product data sheet)

Specifications :

WLL	Speed at full load	Diameter of the steel wire rope	Length of steel wire rope	Maxi lift	Engine output 230 V/50 Hz	Number of rpm motor	Weight of the machine	absorbed current	Dimensions length width height	Packaging dimensions length/height width
kg	m/min	mm	m	m	kW	rpm	Kg	Amp	mm	mm
150	18,5	5	26	25	0,45	1320	39	5	770/520/330	820/500/350