

**Features :**

- Complete installation comprising the ALTOTIR™ 200 winch mounted on a telescopic jib crane (720 to 1120 mm length) with strut for fixing on scaffolding
- Lever for setting to “work” position. This lever can be used to prevent the jib crane rotating during load raising and lowering operations, for safer use
- Noise level 70 db(A)
- Electrical upper limit switch device
- Protection against the phenomenon of overspeed (self-generation) when lowering in the event of a break in the electricity supply
- Protection against on-site voltage variations (210/235 V)
- Oil-immersed geared motor
- Electrical cables in neoprene sheaths for improved resistance to low temperatures up to –25°C
- Patented safety device keeping two turns of steel wire rope constantly wound on the drum to prevent force being applied to the wire rope attachment point
- Supply voltage 230 V single phase 50 Hz
- Direct voltage control via pendant control station with 2 buttons + emergency stop (IP 65 protection) with 1.50 m control cable and plug-in connector

**Options :**

- Direct voltage pendant control station with 2 buttons + emergency stop with 5 m control cable
- 24 V low voltage pendant control station with 2 buttons + emergency stop with 25 m control cable

**Specifications :**

WLL	Speed at full load	Diameter of steel wire rope	Length of steel wire rope	Maxi lift	Engine output 230 V/50 Hz	Number of rpm motor	Weight of the machine	absorbed current	Dimensions length width height	Packaging dimensions length/height/width
kg	m/min	mm	m	m	kW	rpm	Kg	Amp	mm	mm
200	19	5	31	30	0,7	1320	45	7	770(1170)/520/330	820/500/350