

**Features:**

- Lightweight, compact and easy to transport (weight 18 kg)
- Fixes quickly onto tubular structures with flange and spring hook
- Noise level 70 dbA max.
- Electrical upper limit switch device
- Protection against the phenomenon of overspeed (self-generation) when lowering in the event of a break in the electricity supply
- Protection against on-site voltage variations (210/235 V)
- Oil-immersed geared motors
- Electrical cables in neoprene sheaths for improved resistance to low temperatures up to -25°C
- Patented safety device keeping two turns of steel wire rope constantly wound on the drum to prevent force being applied to the wire rope attachment point
- Supply voltage 230 V single phase 50 Hz
- Direct voltage control via pendant control station with 2 buttons + emergency stop (IP 65 protection) with 1.50 m control cable

**Options:**

Jib crane with 0.80 m long arm for fixing winch at end

Jib crane with 1.50 m long arm for fixing winch on moveable trolley

**Specifications :**

WLL	Speed at full load	Diameter of steel wire rope	Length of steel wire rope	Maxi lift	Engine output 230 V/50 Hz	Number of rpm motor	Weight of the machine	Noise level	Absorption	Packaging dimensions length/height/width
kg	m/min	mm	m	m	kW	rpm	Kg	dB(A)	Amp	mm
100	15	3	20,5	20	0,37	1400	18	<70	4,5	300/290/280